



**DYTEC**®  
A CUT ABOVE

# DYTEC-303 CUT-RESISTANT GLOVE WITH MICROFOAM NITRILE COATED PALM



Our latest and greatest cut resistant glove. Meets ANSI cut level A3 and EN388:2016 cut level C. The black microfoam nitrile palm coating along with the premium 18g grey Dytec liner is comfort not felt before in a glove such as this. Excellent abrasion resistance with outstanding dexterity while being extremely lightweight. Improved grip in dry, wet and oily environments. Can be used in a wide variety of applications including aerospace, construction and all types of manufacturing. Available in sizes 7, 8, 9, 10.

## FEATURES

### LINER

Grey **Dytec**® premium,  
18 Gauge

### COATING

Black Microfoam Nitrile  
Palm Coating

## BENEFITS

No Steel or Glass Fiber  
ANSI Cut Level A3  
ISO13997 Cut Level C

Excellent Abrasion Resistance  
Excellent Cut Resistance  
Lightweight

## APPLICATIONS

Aerospace  
Appliance Manufacturing  
Automotive Manufacturing  
Construction  
Glass Work

Logistics  
Packaging  
Metal Fabrication  
Plastic Injection Molding

## CARE INSTRUCTIONS

Recommended washing temperature is between 40°C and 60°C (104–140°F) with mild detergent.

The drying process may cause felting on the fabric surface.  
Drying temperature should not exceed 70°C (158°F)



SKU	Quantity	Unit Of Measure	Size	Colour
14I-DTC303-7	1	12 Pair	(7) Small	Black/Grey
14I-DTC303-8	1	12 Pair	(8) Medium	Black/Grey
14I-DTC303-9	1	12 Pair	(9) Large	Black/Grey
14I-DTC303-10	1	12 Pair	(10) X-Large	Black/Grey