



# Product Family Max Single-Use Earplug

Highest attenuation in single-use earplugs

Learn more about our products at howardleight.com



# **Product Numbers & Ordering Information**

	Product Numbers	Details
Q	3301130	<b>Max - corded</b> SNR 37 H - 36 M - 35 L - 31
1	3301161	<b>Max - uncorded</b> SNR 37 H - 36 M - 35 L - 31

# **Overview**

## **Key Features**

- The world's most-used polyurethane foam earplug
- Bell shape delivers maximum in-ear comfort
- Contoured design easier to insert, resists tendency to back-out of ear canal
- Polyurethane foam enhances comfort, especially for long-term wear
- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up
- Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space

# Recommended Industries/Use

Agriculture
 Chemical
 Construction
 Fire Protection
 Forestry
 Government
 Law Enforcement
 Manufacturing
 Medical
 Military
 Mining
 Municipal Services
 Oil and Gas
 Pharmaceutical
 Steel and Metals
 Transportation
 Utilities
 Welding

#### Hazards

Noise

# Regulations

- 29 CFR 1910.95 OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 Attenuation Test Protocol (US)

# Max Single-Use Earplug - EMEAI

- Part II, (R.S.C. 1985, c. L-2) Canada Labour Code
- Z94.2-1994 Attenuation Test Protocol (CAN)
- 2003/10/EC EU Hearing Directive
- 89/686/EEC EC Directive/PPE
- Category II EC Category/PPE
- EN 352-2:2002 EU Standards
- NOHSC: 1007 (2000) National Standard for Occupational Noise (AUS/NZ)
- NR 15 Security and Health of Work, Annexes 1 and 2, n°3.214/1978 Occupational Noise Regulations (BR)
- ANSI S12.6/1997 Method B Attenuation Test Protocol (BR)
- 9001:2008 ISO

### **Historical Brand**

Howard Leight

# **Specifications**

#### Color

Coral

### Shape

Bell

#### Material

Polyurethane Foam

### **Packaging Options**

• Polybag • Paper Bag • Bulk Refill for Leight Source 400 or Leight Source 500 Dispenser

## **Cord Options**

• • Uncorded • Polycord

# NRR

• 33

## Canada Class

A(L)

## SNR

• 37

#### SLC80

• 26 dB / Class 5

## **EU Certifications**

- European Directives 89/686/EEC
- EC Category PPE Category II
- Standards EN 352-2:2002
- EC Certification Number 1219
- EC Attestation Number 040366
- Laboratory INSPEC

.

## **AUS Certifications**

Standardsmark License #1579

# **Certifications**

**EU Certificate - Max** 

 $http://www.honeywellsafety.com/Supplementary/Documents\_and\_Downloads/Secured/Hearing\_Protection/Earplugs/20038/1033.aspx$ 

EU Certificate - Max

## Max Single-Use Earplug - EMEAI

**EU Certificate - Earplugs** 

 $http://www.honeywellsafety.com/Supplementary/Documents\_and\_Downloads/Secured/Hearing\_Protection/Earplugs/42685/1033.aspx$ 

EC Declaration of conformity The manufacturer SPERIAN HEARING PROTECTION, LLC, 7828 Waterville Rd. San Diego, CA 92154 United States declares that the Personal Protective Equipment (PPE) items listed below, conform with the provisions of Council Directive 89/686/EEC and, where applicable, with the national standard, tr

**EU Certification Report - Max** 

http://www.honeywellsafety.com/Supplementary/Documents\_and\_Downloads/Secured/Hearing\_Protection/Earplugs/20052/1033.aspx

EU Certification Report - Max

# **Literature & Documents**

Instruction Manual - Max (global)

 $http://www.honeywellsafety.com/Supplementary/Documents\_and\_Downloads/Hearing\_Protection/Earplugs/4294986716/1033.aspx$ 

**Earplug Instruction Poster - EN** 

http://www.honeywellsafety.com/Supplementary/Documents\_and\_Downloads/Hearing\_Protection/Earplugs/19799/1033.aspx

# **Training & Proper Use**

- 1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
- 2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
- 3. Hold for 30 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.
- 4. Proper Fit If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.
- 5. Removal Gently twist earplug while slowly pulling in an outward motion for removal.
- Acoustical Check In a noisy environment, with earplugs inserted, cup your hands over your ears and release.
   Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

### **Additional Information**

## **CARE + MAINTENANCE**

- INSPECT Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

© Honeywell International Inc.